


Complete a Building Permit Application form.

Provide plans and/or elevations per Submittal Requirements below.

RESIENTIAL SIDING REPLACEMENT SUBMITTAL REQUIREMENTS



This handout provides submittal requirements if the scope of work is solely to replace siding. If your project is not solely to replace siding, then see <u>Additions & Alterations/Remodels Submittal Requirements.</u>

Acceptable for plans and/or elevations to be hand drawn if legible and drawn with a straight edge. If applying at www.danville.ca.gov/CSS, please apply under permit category Residential Interior

Alterations/Remodels.	
 Please note additional review and submittal items may be required for the following: If your property is located on a Scenic Hill Side or Major Ridge Line, additional Planning Division Review and submittal items may be required. If your property is located in a Wildfire-Urban Interface (WUI) Fire Area, additional Building Division Review and submittal items may be required. Submittal Requirements	
Drawings (3 copies 11"x17" min, 24"x36" max)*	Drawings (3 copies 11"x17" min, 24"x36" max)*
Plan	Plan
 Footprint of the house 	 Footprint of the house
 Location of new siding on Plan 	 Location of new siding on Plan
 Orientation of the home by providing North 	 Orientation of the home by providing North
arrow, street, driveway, etc drawn on the plan	arrow, street, driveway, etc drawn on the plan
 Total area of siding to be replaced. 	 Total area of siding to be replaced.
 Specify type of the existing siding to be removed. 	 Specify on the Plan the siding replaced is to
 Specify type, material, and color of the new 	be replaced like-for-like or in-kind.
siding.	Write the property address on the plans
 Write the property address on the plans 	
Exterior Elevations	
• Required if needed to clarify which areas are to be	Like-for-Like replacement is when you are replacing
resided along elevation.	the siding with the same type, material, and color.
• Label the elevation (e.g. North Elevation, South	

Relevant Code Sections:

CRC R302, CRC 317.1, CRC R703

- For new stucco siding, specify stucco to be three coats minimum when applied over metal lath with 2 layers of grade D paper. CRC R703.7.2 & R703.7.3.
- For new stucco siding, specify weep screed to be installed at the base of the stucco siding. Weep screed shall be a minimum of 2 inches above concrete slabs and 4 inches above exposed earth. CRC R703.7.2.1
- Provide water-resistive barrier per CRC R703.2

Elevation, Front Elevation, etc.)

• Specify wood siding, sheathing and wall framing to be 6 inches above the ground or 2 inches above concrete; or specify material to be pressure treated or decay resistant. CRC R317.1

^{*}Multiple sets are required for submitting in-person. Sheet size requirements apply to in-person & electronic submittals.